

## 60% AMMONIUM NITRATE SOLUTION

### Description

60% Ammonium Nitrate (AN) Solution consists of pure ammonium nitrate and water. TradeMark Nitrogen supplies Industrial AN Solutions in 60% and 83% concentrations. Other strengths can be supplied upon special request.

### Uses

- As a component of explosive mixtures used in mining, quarrying and civil construction
- In the manufacture of catalysts for petroleum refining
- In the production of other nitrate salts

### Handling and Storage

Ammonium Nitrate Solutions should be stored in stainless steel or other corrosion resistant vessels. Pipe lines and fittings should be of similar materials. These solutions must be stored above their salting-out temperatures. Heating coils or heat exchangers must be installed with storage vessels where ambient temperatures below salting-out temperatures are expected for long durations. Always conduct a jar test with new tank mixes to verify compatibility.

### Shipping

60% Ammonium Nitrate Solution is classified as a non-hazardous material by the US Department of Transportation. Shipments are made by rail or tank trucks.



### Chemical & Physical Properties

CAS Number	6484-52-2
Molecular Weight	N/A
Specific Gravity @ 60°F (15.5°C)	1.287
pH	6.0 – 7.0
Salt-Out Temperature	51°F (10.5°C)
Color	Clear
Odor	Little to no detectable odor
Weight per Gallon @ 60°F (15.5°C)	10.73 lbs/gal (1.29 kg/L)
Gallons per ton	186.39

### Typical Analysis

Total Nitrogen	21%
Ammonium Nitrate	60%
Free Ammonia	< 0.02%
Water (Approx)	40%

The data presented herein are believed to be accurate but are in no way guaranteed. TradeMark Nitrogen Corp. makes no warranties, express or implied, that any of the above data is fit for any particular use and expressly disclaims all oral warranties of any kind.

Rev: 2018-02



#### TradeMark Nitrogen Corp.

1216 Old Hopewell Road  
Tampa, Florida 33619 USA  
www.trademarknitrogen.com  
800 452 3107  
813 626 1181